Application No.: 09/683,713 Amendment dated: November 6, 2003 Reply to Office Action of June 17, 2003

This listing of claims will replace all prior versions and listings of claims in this application:

a.) Listing of Claims

- 1. (Currently amended) A double confocal scanning microscope comprising:
 - a light source defining an illuminating beam path with an inherent <u>unmodified</u> illumination point spread function (PSF), the illuminating beam path having a length;
 - a detector defining a detection beam path with an inherent <u>unmodified</u>
 detection point spread function (PSF), and
 - two spaced apart microscope objectives for focusing light propagating along
 the illumination beam path onto a specimen which is disposed in a common
 specimen plane defined by the two microscope objectives, the length of the
 illuminating beam path being the same for both microscope objectives; and
 - at least one optical component disposed in the illuminating or detection beam path, wherein the optical component is configured to vary the amplitude, phase or polarization of the light and thereby to modify a shape of the unmodified illumination PSF of the light in the illuminating beam path to produce a modified illumination PSF and/or of the unmodified detection PSF in the detection beam path to produce a modified detection PSF, wherein secondary maxima of modified and unmodified PSFs are located at different axial positions causing reduction of intensity of secondary maxima of an overall PSF produced by the modified illumination PSF and/or modified detection PSF, of the double confocal scanning microscope
- 3. (Currently amended) The double confocal scanning microscope as defined in Claim I, wherein the <u>unmodified</u> illumination PSF in the illumination beam path and the <u>unmodified</u> detection PSF in the detection beam path shows axially arranged secondary maxima both of which are modifiable as to their shape or position.

- 4. (Currently amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is used to increase the distance between a principal maximum of the modified illumination PSF in the illumination beam path or a principal maximum of the modified detection PSF in the detection beam and secondary maxima.
- 5. (Cancelled)
- 6. (Currently amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is used to locate the secondary maxima of the modified illumination PSF in the illuminating beam path or the modified detection PSF in the detection beam path at different axial positions.
- 8. (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component modulates the wave front of the illuminating light or detection light.
- 9. (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is disposed in a pupil of at least one microscope objective or in a plane optically conjugated therewith.
- (Currently amended) The double confocal scanning microscope as defined in Claim
 wherein the optical component is disposed at any desired location in the
 illuminating beam path or the detection beam path.
- (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is an amplitude filter and a phase filter.

Application No.: 09/683,713

Amendment dated: November 6, 2003 Reply to Office Action of June 17, 2003

- 12. (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is a retardation plate or phase plate.
- 13. (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is an LCD (liquid crystal device) arrangement.
- 14. (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is configured as partially amplitudemodifying elements.
- 15. (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is configured as an adaptive optical system comprising a deformable mirror.
- 16. (Previously amended) The double confocal scanning microscope as defined in Claim 1, wherein the optical component is embodied as a dichroic filter that is disposed in the illuminating beam path or the detection beam path.
- 17. (Cancelled)
- 18. (Cancelled)